

Jawa Motors

Members of Jawad Group

www.jawadgroup.co

QUOTATION SHEET



Note: The picture above is for reference only.

Name	Tanker Trailer	Key Features	Capacity	50,000L
Min. order	One unit		Compartment(s)	7 compartments
Valid period	Within 20 days		Shell material	Carbon steel
			Manhole cover	China brand
Production time	60-65 days		Bottom valve	China brand
			Discharge valve	Ball valve
			Axle	Fuwa, 3 axles
			Suspension	Leaf spring

Shipment: by flat rack container

Payment term:

By T/T, 30% of total amount as down payment, the balance to be paid before delivery .

Condition of price validity:

Any taxes, duties, or charges in importing country shall be covered by buyer.

SPECIFICATION TANKER TRAILER

A. Running system

Item	Standard	Optional
Axle	FUWA brand, 13T, 3 axles,	1st Axle Lifting, BPW/ HUAJIN
Suspension	Leaf spring	Air suspension
King pin	3.5" type, JOST brand, bolted type	2"
Landing gear	JOST E100, operating on right side	JOST A400
Tire	12+1 pieces, 12R22.5 , linglong brand	11R22.5, 13R22.5, double coin brand
Wheel	Steel rim	Aluminum rim
Brake system	China brand ABS	WABCO EBS , WABCO ABS ,

B. Tank Shell

Item	Standard	Optional
Product	Diesel or gasoline	
Tank Shape	Uniform cross section With visible weld line tank sides and tank ends	Varied cross section
Capacity & Compartments	50,000L , ullage distance as per +5% design 7 compartments, 10-5-5-5-5-5-10KL	
Tank shell Material and thickness	Carbon steel, 5.0/Q235	Aluminum/stainless
Tank end and thickness	Carbon steel, 6.0/Q235	
Compartment plate and thickness	Carbon steel, 5.0/Q235	
Anti-wave plate and thickness	Carbon steel, 4.0/Q235	
Frame	Steel	

C. Tank Configuration

Item	Standard	Optional
Man hole	China brand , with 10-inch loading inlet and built-in pressure relief valve,	Civacon brand
Vapor recovery	Without	Civacon brand, China brand, With provision only
Overfill protection	Without	Civacon brand, China brand, With provision only
Gauge marker	1 piece/ compartment,	
Bottom valve	China brand , 4" aluminum alloy pneumatic type,	Civacon brand
Discharge pipeline	Individual pipeline per compartment	
Emergency shut off system	Pneumatic type	

Discharge cabinet	Steel made, right side middle	Aluminum
Discharge valve	China brand, 2.5” aluminum ball valve with cap	API valve
Sight glass flange	Without	
Drip pan	Included	
Product indicator	Included	
Product pump	Without	Vane pump
Flow meter	Without	

D. Other Accessories

	Standard	Optional
Outside ladder	Aluminum made, in front	Steel
Inside ladder	Without	Optional
Top coaming	Included	
Tank top walkway	With anti-skid painting	Welded anti-skid wire-net
Water drain pipe	At back, vertical type,	
Top hand rail	Pneumatic type U shape aluminum collapsible rail, inside of top coaming	Manual type outside of top coaming
Hose carrier	6-meter aluminum circular type	Stainless
Hose	5.5 meter, 2.5” black hose, standard brand	Alfagomma brand
Tool box	One, aluminum made	
Wheel cover	Plastic made, with brush	Steel, Aluminum
Tire cooling	Without	Optional
Rear bumper	High and low bumper, With two red flags, With wire protection between two bumpers	Aluminum
Reverse buzzer	Included	
Fire-extinguisher	8 kg dry powder type, 2 pieces	
Electrical system	24V, LED lamps, 7-pole socket	
Safety cone	1 bracket, 3 cones	
Wheel choke	2 sets	
Rear capacity sign	Without	
Secondary fuel tank	Without	

E. Steel Treatment and Painting

Item	Standard	Optional
Tank inside	Clean, without painting	Anti-rust coating
Tank outside	Sand blasting before painting	
Painting	All white with 3M reflective sticker (Red/White) FLAMMABLE NO SMOKE WITHIN 50 FEET	
Hazchem sticker	Without	

F. Others

As per factory standard.